

VOC Content Test Certificate

Wednesday 23th October 2019

Supplier: Flowcrete Australia Pty Ltd (Unit 2, 41 Deakin Street, Brendale, QLD, 4500).

Sample Description: Flowcrete Deckshield UVWB

Date Tested: October 2019 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D2369-10: 2015 Standard Test Method for Volatile Content of Coatings: Table

1 – Method E with Induction time of 24 hours sat room temperature before putting

in oven.

Test Data:

Specification Green Building Council of Australia Green Star Design & As Built V1.2-13.1.1B Green Star Interiors V1.2-12.1.1B	Flowcrete Deckshield UVWB
One and two pack performance coatings for floors: 140 grams per Litre	15 grams per Litre as VOC content per material

We hereby certify that Flowcrete Deckshield UVWB is below the VOC Content limits of chosen categories specified by Green Star Design, Green Building Council of Australia

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Tuan Duong BE (Chem. Eng.)

Consultant

Luke Morley BSc (Tech) Consultant

V1909075