

Safety Data Sheet

prepared to UN GHS Revision 3

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	F01-307-FUVS-B-HFPWGRY-1.876	Revision Date:	17/11/2020
	Product Name:	Flowseal UV Satin - Hardener B	Supersedes Date:	17/11/2020
1.2	Relevant identified uses of the substance or mixture and uses advised against	Roller application or brushing. Advise against: Spray application, because of multicomponent coatings - Profession removers. Manual activities involving inclusion into/onto article (indoor). Wi (outdoor). For use by appropriately tra	f the additional hazards. Compone al use only. Coatings and paints, th hand contact. Widespread use lea despread use leading to inclusion i	nt of hinners, paint iding to

1.3 Details of the supplier of the safety data sheet

	Manufacturer/Supplier	Tremco CPG Australia Pty Ltd 63 Radley Street Virginia QLD 4014 Australia T. +61 7 3205 7115 F. +61 7 3205 3116 www.flowcreteaustralia.com.au
	Datasheet information obtainable from :	asia@tremcocpg.com
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside US) CHEMTREC +1 703 5273887 (Outside US)

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, RTI Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

hexamethylene diisocyanate, oligomers

HAZARD STATEMENTS

Skin Sensitizer, category 1

H317

May cause an allergic skin reaction.

Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, RTI PRECAUTION PHRASES	H332 H335	Harmful if inhaled. May cause respiratory irritation.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

<u>CAS-No.</u>	Chemical Name	<u>%</u>	
28182-81-2	hexamethylene diisocya	75-100	
822-06-0	Hexamethylene diisocya	0.1 - <1.0	
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
28182-81-2	GHS07	H317-332-335	0
822-06-0	GHS06-GHS08	H315-317-319-331-334-335	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Do not use solvent or thinners to clean skin. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. AFTER EYE CONTACT: Consult a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. Harmful by inhalation. Irritating to respiratory system. Limited evidence of a carcinogenic effect. Irritating to eyes and skin. May cause sensitization by inhalation and skin contact.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire. Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide, nitrogen oxide, cyanides, isocyanate vapours.

5.3 Advice for firefighters

Use water spray to cool unopened containers. Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. For personal protection see section 8.2. Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Discharge into the environment must be avoided. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: People handling polyurethane products must have received special training according to guidelines from the National Occupational Health and Safety Board. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Apply technical measures to comply with the occupational exposure limits (see section 8).

PROTECTION AND HYGIENE MEASURES: Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze. **STORAGE CONDITIONS:** Keep out of the reach of children. Keep at temperatures between 10 and 30 °C. Store in original container. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.3 Specific end use(s)

Component of multicomponent coatings. The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (AU)

Name	CAS-No.	<u>TWA ppm</u>	STEL ppm	TWA mg/m3	STEL mg/m3
hexamethylene diisocyanate, oligomers	28182-81-2				
Hexamethylene diisocyanate	822-06-0			0.02	0.07
Name	CAS-No.	OEL Note			
hexamethylene diisocyanate, oligomers	28182-81-2				
Hexamethylene diisocyanate	822-06-0				

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment. Combination filter: A2-P2.

EYE PROTECTION: Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Isocyanates can harden gloves and increase the risk of their splitting. Protective gloves complying with EN 374: Viton®, Neoprene, Nitril rubber, Butyl rubber. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** At temperatures below 30°C, provide a good standard of general ventilation. At temperatures over 30°C - and always if sprayed - exhaust ventilation is required. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties Appearance:

Appearance:	Liquid, yellowish
Physical State	Liquid
Odor	Almost odourless
Odor threshold	Not determined
рН	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	82 - N.D.
Flash Point, (°C)	158
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	

		1.16 at 20°C
	Solubility in / Miscibility with water	Insoluble
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	Not determined
	Explosive properties	Not determined
	Oxidising properties	Not determined
2	Other information	
	VOC Content g/I:	Not determined
	Specific Gravity (g/cm3)	1.160

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.3 Possibility of hazardous reactions

Polymerises at about 200°C with evolution of CO2. Amines and alcohols cause exothermic reactions. Preparation reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze.

10.5 Incompatible materials

Keep away from oxidising agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Preparation reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity: Oral LD50: Inhalation LC50:	No information available. No information available.
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
28182-81-2	hexamethylene diisocyanate, oligomers	5000 mg/kg, oral, rat		18500 mg/ m3/1H inhalation, rat	0.000	0.000
822-06-0	Hexamethylene diisocyanate	Rat - male - 726 (OECD TG 401)	>7000	Rat - male and female - 0.124 mg/l - 4 h (OECD TG 403)		

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Isocyanates may cause acute irritation and/or sensitisation of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition.

12.	Ecological Information	
12.1	Toxicity:	
	EC50 48hr (Daphnia):	No information
	IC50 72hr (Algae):	No information
	LC50 96hr (fish):	No information
12.2	Persistence and degradability:	The polyurea produced on contact with water is insoluble, inert and non- biodegradable.
12.3	Bioaccumulative potential:	No information

822-06-0

8.8 mg/L (Brachydanio rerio)

77,4 mg/l (ErC50, static,

desmodesmus subspicatus)

12.4 Mobility in soil:		No information					
12.5 Results of PBT and vPvB assessment:		The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.					
12.6	Other		The polyisocya insoluble.produ	nate reacts with ct with high me		erface forming CO2 and a solid irea). This reaction is accelerate	d by
<u>CAS-</u>	No.	Chemical Name	<u>EC50 4</u>	<u>8hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>	
28182	2-81-2	hexamethylene diisocyanate, oligomers	No infor	mation	No information		

No information

13. Disposal Considerations

Hexamethylene diisocyanate

13.1 WASTE TREATMENT METHODS: Dispose of waste material at an approved hazardous waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Contaminated packaging to be disposed of as product. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

Transport Information	
UN number	Not applicable
UN proper shipping name	Not applicable
Technical name	Not applicable
Transport hazard class(es)	Not applicable
Subsidiary shipping hazard	Not applicable
Packing group	Not applicable
Environmental hazards	Not applicable
Special precautions for user	Not applicable
EmS-No.:	Not applicable
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable
ADG Hazchem Code	Not applicable
	UN number UN proper shipping name Technical name Transport hazard class(es) Subsidiary shipping hazard Packing group Environmental hazards Special precautions for user EmS-No.: Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Please contact Manufacturer / Supplier for details related to inventory listing of national regulations.

Australia Australia Inventory of Industrial Chemicals (AIIC) China Inventory of Existing Chemical Substances (IECSC) Japan Inventory of Existing and New Chemical Substances (ENCS) Korea Korea Existing Chemicals Inventory (KECI) New Zealand New Zealand Inventory of Chemicals (NZIoC) Philippines Philippines Inven tory of Chemicals and Chemical Substances (PICCS) Taiwan Taiwan Chemical Substance Inventory (TCSI) Thailand Thailand Existing Chemicals Inventory (TECI) Vietnam National Chemical Inventory (NCI)

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.

Reasons for revision

Composition Information Changed Substance and/or Product Properties Changed in Section(s): 01 - Identification 02 - Hazard Identification 03 - Composition/Information On Ingredients 05 - Fire-fighting Measures 08 - Exposure Controls/Personal Protection 09 - Physical and Chemical Properties 15 - Regulatory Information

Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830; European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP EC EU	Classification, Labeling & Packaging Regulation European Commission European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%

Date Printed: 18/11/2020

EC50	Half maximal effective concentration	
IC50	Half maximal inhibitory concentration	
PBT	Persistent bioaccumulative toxic chemical	
vPvB	Very persistent and very bioaccumulative	
EEC	European Economic Community	
ADR	International Transport of Dangerous Goods by Road	
RID	International Transport of Dangerous Goods by Rail	
UN	United Nations	
IMDG	International Maritime Dangerous Goods Code	
IATA	International Air Transport Association	
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as	
modified by the Protocol of 1978		
IBC	International Bulk Container	
RTI	Respiratory Tract Irritation	
NE	Narcotic Effects	

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.